

GSA Class 5 Vault Door Order Form



BROWN SAFE

Brown Safe Manufacturing, Inc.
 1081 Poinsettia Ave. Vista, CA 92078
 Phone: 760-233-2293
 Fax: 760-233-2297
 E-mail: Sales@BrownSafe.com

Disclaimer: The number and/or types of vault doors requested on this order form are the number and types of vault doors that will be put into production, regardless of any previous documentation, specifications, and/or discussion. It is highly recommended that you carefully review the information below when making your selections to avoid any costly mistakes and/or errors. Once you have completed our order form, please sign and return it to us via e-mail, mail, or fax. Your order will not be considered complete nor put into production until a signed copy of this order form is received. This signed confirmation acknowledges your acceptance that all items are correct and to proceed forward with production as indicated on our order form.

| | |
|--------------------------------|-------------------------|
| Customer Name: _____ | Shipping Address: _____ |
| Customer Contact: _____ | _____ |
| Purchase Order No.: _____ | _____ |
| Project Name: _____ | _____ |
| Requested Delivery Date: _____ | _____ |

| | |
|--|--|
| Door Type: GSA Class 5-A Armory Vault Door <input type="checkbox"/> GSA Class 5-B Ballistic Vault Door <input type="checkbox"/> GSA Class 5-V Security Vault Door <input type="checkbox"/> | Specify Type of Day Gate: No Day Gate Required <input type="checkbox"/> Standard Day Gate <input type="checkbox"/> Standard Day Gate with Arms/Issue Port <input type="checkbox"/> Dutch-Style Day Gate <input type="checkbox"/> Dutch-Style Day Gate with Arms/Issue Port <input type="checkbox"/> |
| Door Swing: Right Swing <input type="checkbox"/> Left Swing <input type="checkbox"/> Double-Leaf <input type="checkbox"/> | Please Note: Day gates will swing into the vault and will be hinged on the same side as its corresponding vault door. All arms/issue ports will be 8"H x 12"W. |
| Optical Viewer/Device: View from inside to outside of vault <input type="checkbox"/> View from outside to inside of vault <input type="checkbox"/> No optical viewer/device required <input type="checkbox"/> | Specify Type of Day Gate Entry Device: Single-Cylinder Dead Bolt <input type="checkbox"/> Single-Cylinder Dead Latch <input type="checkbox"/> Double-Cylinder Dead Bolt <input type="checkbox"/> Single-Cylinder Dead Latch <input type="checkbox"/> Dual-Handle Lever Lock Option <input type="checkbox"/> |
| Wall Thickness: Please specify your desired wall thickness <input style="width: 50px;" type="text"/> " <small>6" - 12" flanges are included in the cost of each vault door. Custom charges will be applied for any wall thickness/flanges outside our standard wall thickness: 6" - 12".</small> | Please Note: All single and double-cylinder dead bolt/dead latch options come standard with a pull handle. IMPORTANT: Any requests for entry device options other than our standard offerings will result in an additional cost. |
| | Quantity <input style="width: 50px;" type="text"/> |

GENERAL INFORMATION

GSA Class 5 vault doors are only built as outswing vault doors and are all equipped with an emergency inner-escape device.

Single-leaf vault doors (single door) have a clear-door opening of 78"H x 40"W and a rough opening of 82.5"H x 48"W.

Double-leaf vault doors (double door) have a clear door opening of 78"H x 80"W and a rough opening of 82.5"H x 88"W.

All GSA Class 5 vault doors must be built to federal specification AA-D-600 (latest revision) to bear GSA label and will be painted in a textured grey finish in accordance to federal standard 595 (color no. 26134).

Brown Safe does not install or provide final inspection of GSA Class 5 vault doors nor are GSA Class 5 vault intended for exterior applications.

CLASS 5 PROTECTION

These are U.S. government Class 5 vault doors, which have been tested and approved by the government under federal specification AA-D-600 (latest revision).

GSA Class 5-A Armory Vault Door Protection:
 30 man minutes covert entry
 10 man minutes forced entry

GSA Class 5-B Ballistic Vault Door Protection:
 20 man hours surreptitious entry minutes covert entry
 30 man minutes covert entry
 10 man minutes forced entry
 Ballistic resistant

GSA Class 5-V Security Vault Door Protection:
 20 man hours surreptitious entry minutes covert entry
 30 man minutes covert entry
 10 man minutes forced entry

LOCK SPECIFICATIONS

PLEASE NOTE:

The only difference between the armory vault door and security vault door is the type of lock that is installed. Security vault doors and the ballistic vault doors can be used to house classified material. Armory vault doors can be used to house non-classified material. If you are unsure which lock you need, please contact us to discuss your options and it is always a great idea to contact the final inspecting officer to confirm their lock expectations in order to avoid future issues.

Federal specification AA-D-600 (latest revision) requires that the locks used on GSA approved vault doors meet the following requirements:
 GSA Class 5-A armory vault doors must have locks that meet federal specification FF-L-2937 (latest revision).
 GSA Class 5-B ballistic vault doors and 5-V security vault doors must have locks that meet federal specification FF-L-2740 (latest revision).